

´		Dimensions	in Inches withou	Flow Rate in Gallons				
Meter Model	Meter Size	Housing Material	A Meter Length	B Centerline to Base	Meter Length with Conn.	Cold Liquids 32120° F	Chemicals & Oils 32250° F (BZ) 32100° F (PL)	Approx. Weight
M25	5/8"	BZ or PL	7-1/2"	1-3/8"	12-7/16"	1/225 gpm	125 gpm	5 lb
M25	3/4"	BZ or PL	7-1/2"	1-3/8"	12-5/8"	1/2 30 gpm	130 gpm	5 lb
M35	3/4"	BZ	9"	1-3/4"	14-1/8"	3/4 35 gpm	N/A	6 lb
M40	1"	PL	10-3/4°	2-1/4"	16-3/16"	3/4 50 gpm	N/A	5 lb
M70	1"	BZ	10-3/4"	2-1/4"	16-5/8"	170 gpm	570 gpm	12 lb
M120	1-1/2"	BZ	12-5/8"	2-5/8"	19-3/4"	2120 gpm	*See Note	20 lb
M170	2"	BZ	15-1/4"	3-3/8"	22-7/8"	2170 gpm	N/A	30 lb

R7 = Bronze; PI = Plastic

N/A = Not available in high temperature/chemical option.

*Note: Available for chemicals or fluids not to exceed 110° F (43° C). NPT connection set assemblies available.

Height Dimensions in Inches with Register and Accessories							
Meter Size	With Non Resettable Register	With Transmitter	With MS-ER1 Transmitter	With ECA Transmitter	With 258 Register	With Series 76 Register	
5/8" & 5/8 x 3/4"	5-3/4"	7-3/8"	11-1/4"	9-3/8"	8"	15-1/4"	
3/4"	6-1/8"	7-3/4"	11-5/8"	9-3/8"	8-3/8"	15-5/8"	
1"	7-1/2"	9-1/8"	13"	11-3/16"	9-3/4"	17"	
1-1/2"	9-1/8"	10-3/8"	14-1/4"	12-3/4"	11"	18-1/4"	
2"	10-3/4"	12-1/4"	16-1/8"	14-3/8"	12-7/8"	20-1/8"	

MATERIALS OF CONSTRUCTION

2	Cold Liquid Units	High Temp. and/or Chemical Units Models 25 & 70		
Housing	BZ or PL	BZ: 250° F, PL: 100° F		
Chamber	Noryl	LCP		
Disc	SAN	LCP		
Crossbar	Nylon	Ultem		
Magnetic Assembly	Nylon	Ultem		
Chamber Retainer	Polyethylene	Metal Clip		
Screen	Polypropylene	None		