Donaldson.

BIN VENT DUST COLLECTOR

MODELS TBV-2, TBV-4, TBV-6

Cartridge filtration technology that adds economic value and recovers valuable dust.

- Efficient, compact design for applications involving silos, storage bins, or conveyor transfer points
- Available as plenum-mounted and insertable cabinets to keep the profile low
- Units are easily installed on bins or silos, eliminating ductwork and reducing installation expenses
- Standard Ultra-Web[®] cartridge filters, with fine fiber technology, provide higher filtration efficiency and longer filter life
- MERV* 15 filtration efficiency per ASHRAE 52.2-2007
- Choice of filter cartridges provide high filtration efficiency for a wide variety of applications

Designed for easy filter service and maintenance – no tools required.

- Easy filter removal and replacement from clean air side makes it unnecessary to enter the silo or storage container
- Continuous-duty, on-demand pulse cleaning provides uninterrupted service and keeps filters clean for a long time







TBV-4 with Plenum

* The Minimum Efficiency Reporting Value (MERV) of this filter cartridge has been determined through independent laboratory testing using ASHRAE 52.2 (2007) test standards.

The MERV rating was determined at a face velocity of 118 feet (36.0 meters) per minute and loading up to four inches (101.6 millimeters) water gauge. Actual efficiency of any filter cartridge will vary according to the specific application parameters. Dust concentration, airflow, particle characteristics, and pulse cleaning methods all affect filtration efficiency.

DIMENSIONS & SPECIFICATIONS





	Filter Area							
Models	Ultra-Web		Fibra-Web Ultra-Tek		Torit-Tex		No. of Cartridges	No. of Valves
	ft²	m²	ft²	m²	ft²	m²		
TBV-2	452	42.0	220	20.4	100	9.3	2	2
TBV-4	904	84.0	440	40.9	200	18.6	4	2
TBV-6	1,356	126.0	660	61.3	300	27.9	6	3

Dimensions **Shipping Weight** В С D Α Models Plenum Insertable Plenum Insertable lb in mm in mm in mm in mm in mm kg lb kg TBV-2 34.6 878.8 53.6 1361.4 33.1 840.7 24.2 614.7 37.5 952.5 441 200.0 377 171.0 TBV-4 34.6 878.8 54.6 1386.8 34.1 866.1 35.4 899.2 37.5 952.5 702 318.4 627 284.4 TBV-6 1318.3 54.6 1386.8 34.1 866.1 35.4 899.2 54.7 1389.4 792 359.2 702 318.4 51.9

STANDARD FEATURES & AVAILABLE OPTIONS

STANDARD	OPTIONAL				
Ultra-Web [®] cartridge	Insertable or plenum style				
Magnehelic ^{®*} gauge	Cartridges				
NEMA 4 enclosure	Ultra-Web [®] FR Fibra-Web [®] & Fibra-Web FR				
10-year warranty	• Ultra-Tek [®] • Torit-Tex [™]				
	Weatherhood				
	1, 2, 3, and 5 hp fans				
	Dampers				
	Chamber silencers				
	Photohelic** gauge				
	NEMA 9 enclosure				
* Magnehelic and Photohelic are registered trademarks of Dwyer Instruments, Inc.	Hostile environment coating				

Important Notice

Many factors beyond the control of Donaldson can affect the use and performance of Donaldson products in a particular application, including the conditions under which the product is used. Since these factors are uniquely within the user's knowledge and control, it is essential the user evaluate the products to determine whether the product is fit for the particular purpose and suitable for the user's application. All products, product specifications, availability and data are subject to change without notice, and may vary by region or country.



Significantly improve the performance of your collector with genuine Donaldson Torit replacement filters and parts. **Call Donaldson Torit today 800-365-1331.**

Donaldson Company, Inc. Torit P.O. Box 1299 Minneapolis, MN 55440-1299 U.S.A. donaldsontorit.com Tel 800-365-1331 (USA) Tel 800-343-3639 (within Mexico) donaldsontorit@donaldson.com

EXACTLY WHAT YOU NEED."

F118111 ENG (08/16) Bin Vent Collector ©2016 Donaldson Company, Inc. Donaldson, Torit, Ultra-Web, Ultra-Tek, Fibra-Web, Torit-Tex and the color blue are marks of Donaldson Company, Inc. All other marks belong to their respective owners.